



**FLOOR PROTECTION:**

- ALL FLOOR PROTECTION SPECIFICATIONS ARE MINIMUM REQUIREMENTS. THE DEPTH OF EACH FLOOR PROTECTOR IS RELATED TO THE HEIGHT OF THE FIREBOX FROM THE FLOOR. REFER TO THE DEPTH/HEIGHT CHART. A MINIMUM DEPTH OF 300mm MUST BE MAINTAINED  
 - FOR NON-COMBUSTIBLE FLOORS, FLOOR PROTECTION IS NOT NECESSARY, HOWEVER IT IS RECOMMENDED THAT IF FLOOR COVERINGS USED, EG: CARPET, TIMBER OR VINYL THAT THE COVERING BE TRIMMED TO THE MINIMUM CLEARANCES  
 - FOR COMBUSTIBLE FLOORS OR RAISED PLINTHS THE BROADY'S INSULATED PLINTH BENEATH THE FIREBOX AND 75mm WOODTEX FLOOR PROTECTOR IN FRONT TO MINIMUM DEPTH MUST BE USED. THE COMBINATION OF THESE TWO PLUS TILES OR SLATE ETC. TOTALS A 90mm HEIGHT FOR THE FLOOR PROTECTOR. REFER TO INSTALLATION REQUIREMENTS

**SEISMIC RESTRAINT:**

- SECURE WITH 2xCS 'DYN0' BOLTS THROUGH FLOOR OF FIREBOX INTO CONCRETE BASE



SPECIALISING IN COOKERS, WOODSTOVES & FIREPLACES SINCE 1885

**TITLE:**  
**B750 FIRE BOX**  
 BRICK/MASONRY INSTALL  
 ONTO CONCRETE FLOOR

**SCALE:**  
 A4 1:20

**DATE:**  
 FEB 06

**BROADY'S NZ LIMITED**

46a SIR WILLIAM AVENUE, EAST TAMAKI  
 PO BOX 58-183-GREENMOUNT, AUCKLAND  
 www.broadys.co.nz  
 T. +64 9 274 0658 F. +64 9 272 2519

NOTE: FIREBOX TO SIT ON FLOOR FINISH, LITLES, AS TO NOT BLOCK AIR VENT